BioSmart™

Therapeutic Infrared Heat

SUPPLIED BY:

MIGHTY ENERGY SOLUTIONS

sales@MIGHTYENERGY.net
206-715-0893
MIGHTYENERGY.net

BIO-1000F In-Wall Edition

All metal **Chassis**, 22 & 24 gauge, with synthetic, paintable shell

Chassis size is 16" × 12 5/8" × 4" (HxWxD) / 13 lbs

120 volt or 220 volt AC, 1000 watt **Power Requirement**

4800 BTU equivalent **Heat Output**

Ceramic insulated plate **Infrared Emitters**

40,000 hour **Emitter Life Expectancy**

Safety Cut-Off prevents damage to the unit

Chassis Safety Insulation exceeds all government and independent laboratory standards for safety

cTUVus Int'l **Certification** (UL/CSA equivalent)

Zoned Heat Capability: Pre-wired - simple two-wire contact to any zone control panel

Proprietary **Heating Chamber** with copper-ion generation panels

Heats with **safe, therapeutic Far-Infrared** waves

System Noise Level is only 18 dB

Thermostat Type: Any standard digital, programmable, or mechanical (no in line high voltage)

Installation: Any wall with a minimum 3 ½ inches of depth

Rough opening is 15 ½" × 12 ¾" (HxW)

Save energy with **Zoned-Heating Capability**

25 years+ **Life Expectancy**

5-Year **Limited Warranty**

©2014 Copyright BioSmart Technologies CF1